

Texmate Classic Digital Panel Meters and Bargraphs

Reliable, robust and cost effective digital panel meters for all of your process monitoring needs. Field proven for over 40 years. Accommodate a wide range of sensor and process inputs. Each model provides a dedicated measurement. Highest quality, MADE IN USA!

- OEM's choice for digital display indicators – **Proven Performance @ Competitive Pricing**
- 3.5, 4.0, 4.5, 5, 6 and Dual-8 Digit and Bargraph display options
- Standard DIN, NEMA and Texmate enclosure size options including miniature and short depth
- Input Signal options include 4-20mA, VAC, AAC, frequency, V/mVDC, temperature, and 4 digit remote/slave BCD display
- Wide variety of 4-20mA Loop Powered options, from simple indicators (**World's Lowest 1V Loop Drop**) to advanced controller/totalizers with pulse output or alarm-on/off control for flow and batch operations
- Large selection of Economical, high quality DC volt meters in a variety of enclosure sizes, many under \$100 list price
- See our website (www.texmate.com) for a variety of color options for each meter (default color is red, other options include green, high brightness red, amber, and blue)
- Need something special, like an indicator with 4-20mA output, or up to four independent dry contacts for alarms/control, or a higher resolution 101-segment bargraph? Call us or check out the UL Certified Lynx and Leopard indicators/controllers on our website!!



Popular DU family upgraded to Lynx DX equivalent, most at same or lower cost!

- More Efficient, Universal, Auto-Sensing Switching Power Supply – Save Energy!
- Same enclosure size
- Larger Digit Size option (0.8", 0.56" standard)
- UL Certified!



4-20mA Process Meters – Our most comprehensive line up

Major Feature Selector

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> Miniature	<input type="checkbox"/> 31 Segment Bargraph	<input type="checkbox"/> 5VDC	<input type="checkbox"/> None	<input type="checkbox"/> Linear Only
<input type="checkbox"/> Short Depth	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> 9-36VDC/VAC	<input type="checkbox"/> 1 Relay	<input type="checkbox"/> Set display to any +/- range
<input type="checkbox"/> 1/32 DIN	<input type="checkbox"/> 3.5 Digit (LCD)	<input type="checkbox"/> Loop Powered	<input type="checkbox"/> 2 Relay	<input type="checkbox"/> Programmable Setup
<input type="checkbox"/> NEMA	<input type="checkbox"/> 4.5 Digit (7 segment)	<input type="checkbox"/> Universal Line Voltage	<input type="checkbox"/> 1 SSR	<input type="checkbox"/> Advanced Programmable Functions
<input type="checkbox"/> 1/8 DIN	<input type="checkbox"/> 5 Digit (LCD)			
<input type="checkbox"/> 1/16 DIN	<input type="checkbox"/> 6 Digit (LCD)			
	<input type="checkbox"/> Dual 8 Digit (LCD)			

AC Volts

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> NEMA	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> Universal Line Voltage	<input type="checkbox"/> None	<input type="checkbox"/> Averaging – UL Certified
<input type="checkbox"/> 1/8 DIN	<input type="checkbox"/> 4 Digit (7 segment)	<input type="checkbox"/> Line Voltage	<input type="checkbox"/> 1 Relay	<input type="checkbox"/> True RMS – UL Certified
<input type="checkbox"/> 1/16 DIN	<input type="checkbox"/> 3.5 Digit (LCD)	<input type="checkbox"/> 9-36VDC/VAC	<input type="checkbox"/> 2 Relay	<input type="checkbox"/> Averaging

■ AC Amps

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> NEMA	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> Universal Line Voltage	<input type="checkbox"/> None	<input type="checkbox"/> Averaging – UL Certified
<input type="checkbox"/> 1/8 DIN	<input type="checkbox"/> 4 Digit (7 segment)	<input type="checkbox"/> Line Voltage		<input type="checkbox"/> True RMS – UL Certified
		<input type="checkbox"/> 9-36VDC/VAC		<input type="checkbox"/> Averaging 1A
				<input type="checkbox"/> Averaging 5A

■ Line Voltage & Frequency

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> 1/16 DIN	<input type="checkbox"/> Dual 4 Digit (7 segment)	<input type="checkbox"/> Universal Line Voltage	<input type="checkbox"/> None	<input type="checkbox"/> Averaging 30-300VAC + 50-400Hertz

■ Line Frequency

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> 1/8 DIN	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> Line Voltage	<input type="checkbox"/> None	<input type="checkbox"/> 100-140VAC Line Frequency
		<input type="checkbox"/> 15-48VDC/VAC		

■ DC Volts (ranges include 2-200V, 20-200mV, 50-100mV)

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> Miniature	<input type="checkbox"/> 20 Segment Bargraph	<input type="checkbox"/> 5VDC	<input type="checkbox"/> VDC Excit.	<input type="checkbox"/> Unipolar
<input type="checkbox"/> Slim Bezel	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> 12, 15, 24VDC	<input type="checkbox"/> BCD	<input type="checkbox"/> Bipolar
<input type="checkbox"/> 1/16 DIN	<input type="checkbox"/> 3.5 Digit (LCD)	<input type="checkbox"/> 9-36VDC / 12-24VAC		<input type="checkbox"/> Differential
<input type="checkbox"/> Short Depth	<input type="checkbox"/> 4.5 Digit (7 segment)	<input type="checkbox"/> Universal Line Voltage		<input type="checkbox"/> Low Power (25mW)
<input type="checkbox"/> NEMA		<input type="checkbox"/> Line Voltage		<input type="checkbox"/> Economical
<input type="checkbox"/> 1/8 DIN				

■ Temperature

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> NEMA	<input type="checkbox"/> 3.5 Digit (7 segment)	<input type="checkbox"/> Line Voltage	<input type="checkbox"/> None	<input type="checkbox"/> T/C, J Type (0-1400°F)
<input type="checkbox"/> 1/8 DIN		<input type="checkbox"/> 9-36VDC/VAC		<input type="checkbox"/> T/C, J Type (0-760°C)
				<input type="checkbox"/> T/C, K Type (0-1999°F)
				<input type="checkbox"/> T/C, J Type (0-1260°C)

■ BCD (Binary Coded Decimal, sensor or PLC output)

Enclosure	Display	Power Supply	Outputs	Special Functions
<input type="checkbox"/> 1/16 DIN	<input type="checkbox"/> 4 Digit (7 segment)	<input type="checkbox"/> 5VDC	<input type="checkbox"/> None	<input type="checkbox"/> Parallel or Multiplexed BCD



- For ordering info call: 1-800-TEXMATE or 760 598-9899
- Email: orders@texmate.com
- 450 State Place, Escondido, CA 92029

www.texmate.com